

Google Analytics Regular Expressions Cheat Sheet by Jay Taylor (Jay Taylor) via cheatography.com/573/cs/243/

Anchors Start of line \$ End of line **Character Classes** White space character \s \S Non-white space character Digit character \d Non-digit character \D \W Non-word (e.g. punctuation, spaces)

Metacharacters (must be escaped)			
٨	[]	
\$	()	
	{	}	
*	+	?	
\	I	-	

GAT litter group accessors		
\$Ax	Access group x in field A (e.g. \$A1)	
\$Bx	Access group x in field B (e.g. \$B1)	



By Jay Taylor (Jay Taylor) cheatography.com/jay-taylor/ www.alpari.co.uik

Quantifiers		
*	Zero or more (greedy)	
*?	Zero or more (lazy)	
+	One or more (greedy)	
+?	One or more (lazy)	
?	Zero or one (greedy)	
??	Zero or one (lazy)	
{X}	Exactly X (e.g. 3)	
$\{X,\}$	X or more, (e.g. 3)	
{X, Y}	Between X and Y (e.g. 3 and 5) (lazy)	

Ranges and Groups		
Any character		
a or b (case sensitive)		
Group, e.g. (keyword)		
Passive group, e.g. (?:keyword)		
Range (a or b or c)		
Negative range (not a or b or c)		
Uppercase letter between A and Z		
Lowercase letter between a and z		
Digit between 0 and 7		

Published 10th February, 2012. Last updated 1st June, 2014. Page 1 of 1.

Sample Patterns

^/directory/(.*)

Any page URLs starting with /directory/

(brand\s*?term)

Brand term with or without whitespace between words

^brand\s+[^cf]

Key phrases beginning with 'brand' and the second word not starting with c or f

URLs ending in '.aspx'

ORDER\-\d{6}

"ORDER-" followed by a six digit ID

(?:\?|&)utm=([^&\$]+)

Value of 'utm' querystring parameter

Sponsored by Readability-Score.com

Measure your website readability!

https://readability-score.com